

## Section 1. Chemical Product and Company Identification

<b>Product name</b> <b>Blueshield:</b> 650-308L; 650P-308L; 652-316L; 652P-316L; 653-347; 654-309L; 654P-309L; LEXAL 2209; LEXAL 2209P;	<b>Classification</b> <b>CSA:</b> E308LT0-1,4; E308LT1-1,4; E316LT0-1,4; E316LT1-1,4; E316LT1-1,4; E309LT0-1,4; E309LT1-1,4; E2209LT0-1,4; E2209LT1-1,4;	<b>Classification</b> <b>AWS:</b> E308LT0-1,4; E308LT1-1,4; E316LT0-1,4; E316LT1-1,4; E316LT1-1,4; E309LT0-1,4; E309LT1-1,4; E2209LT0-1,4; E2209LT1-1,4;
<b>Description</b> : FCAW Stainless Consumables <b>In case of emergency</b> : 1-514-878-1667 <b>Supplier</b> : Air Liquide Canada Inc. 1250, René-Lévesque West, Suite 1700, Montreal, QC H3B 5E6	<b>Generic Code</b> : AL-T-014-0 <b>Date of issue</b> : 01/30/2008	

## Section 2. Hazards Identification

<b>Physical state and Appearance</b>	: Solid.
<b>Emergency overview</b>	: <b>These hazards relate to welding fumes (electrodes in use) and not to the electrodes as sold.</b>  WARNING! ELECTRIC SHOCK can kill. FUMES AND GASES can be dangerous to your health. ARC RAYS can injure eyes and burn skin. SUSPECT CANCER HAZARD. MAY CAUSE CANCER. CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING ORGANS: BLOOD, KIDNEYS, LUNGS, LIVER, RESPIRATORY TRACT, SKIN, CENTRAL NERVOUS SYSTEM, EYES, NOSE, SINUSES. MAY BE HARMFUL IF INHALED. MAY CAUSE EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION.
<b>Routes of entry</b>	: Absorbed through skin. Dermal contact. Eye contact. Inhalation.
<b>Potential acute health effects</b>	<p><b>Eyes</b> : Very hazardous by the following route of exposure: of eye contact (irritant). Inflammation of the eye is characterized by redness, watering and itching.</p> <p><b>Skin</b> : Hazardous by the following route of exposure: of skin contact (sensitizer). Skin contact may produce burns.</p> <p><b>Inhalation</b> : Hazardous by the following route of exposure: of inhalation.</p> <p><b>Ingestion</b> : Since the product (welding fumes) is a gas and that it is mostly probable that it will be inhaled more than ingested, please consider first to look at the preventive measures in case of inhalation.</p>
<b>Potential chronic health effects</b>	: <b>Carcinogenic effects(*)</b> : Classified None. by NIOSH [Chromium]. Classified A4 by ACGIH, 3 by IARC [Chromium]. Classified + by NIOSH [Nickel]. Classified 2B by IARC, Classified 2 by NTP [Nickel]. Classified A5 by ACGIH [Nickel]. Classified 2B by IARC [Titanium dioxide]. Classified None. by NIOSH [Titanium dioxide]. Classified A4 by ACGIH [Titanium dioxide]. Classified 1 by NTP, + by NIOSH [Silica crystalline quartz]. Classified A2 by ACGIH, 2A by IARC [Silica crystalline quartz]. Classified A4 by ACGIH [Zirconium oxide]. Classified None. by NIOSH [Alumina]. Classified A4 by ACGIH [Alumina]. Classified A4 by ACGIH, 3 by IARC [Calcium fluoride]. <b>MUTAGENIC EFFECTS</b> : Not available. <b>TERATOGENIC EFFECTS</b> : Not available.
<b>Medical conditions aggravated by over-exposure</b>	: Repeated exposure to the fumes emitted while using this material may produce general deterioration of health.
(*) See Abbreviations (section 16).	

## Section 3. Composition, Information on Ingredients

Name	CAS #	% by weight	UN number
Chromium, Metal	7440-47-3	16-25	Not applicable.
Nickel	7440-02-0	8-15	Not applicable.
Titanium dioxide	13463-67-7	2-12	Not applicable.
Manganese	7439-96-5	0.5-4	Not applicable.
Molybdenum	7439-98-7	0.01-5	Not applicable.
Silica, Crystalline - Quartz	14808-60-7	0.01-3	Not applicable.
Zirconium oxide	10101-52-7	0.01-3	Not applicable.

The fumes emitted by the electrodes, in use, are hazardous. This MSDS is written for workers using these electrodes.

See Section 8 for Exposure Limits of the oxides found in the welding fumes.

## Section 4. First Aid Measures

- Eye contact** : Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention immediately.
- Skin contact** : Wash with soap and water. Get medical attention if irritation develops.
- Inhalation** : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion** : Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.

## Section 5. Fire Fighting Measures

- Flammability of the product** : Non-flammable. Emits toxic fumes when heated.
- Explosibility** : Non-explosive in the presence of open flames, sparks and static discharge, of shocks, of heat.
- Fire-fighting media and instructions** : Use extinguishing media suitable for surrounding materials.

## Section 6. Accidental Release Measures

- Small/Large Spill and Leak** : Use appropriate tools to transfer the spilled solid to a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

## Section 7. Handling and Storage

- Handling** : Avoid breathing dusts, vapors or fumes from burning materials. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Do not ingest. Keep container closed. Wash thoroughly after handling.
- Storage** : All filler metals in their original, unopened containers should be kept in a relatively dry storage area at temperatures between 15°C (60°F) and 30°C (80°F) and 50% maximum relative humidity.

## Section 8. Exposure Controls, Personal Protection

- Engineering controls** : Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

### Personal protection

- Eyes** : Safety glasses with side shields. Face shield with radiation shielding.
- Body** : Full suit. (Fire resistant.)
- Respiratory** : Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear a canister breathing apparatus (respirator) or a supplied-air respirator, when required, to weld in a confined space or when room exhaust or ventilation does not keep exposure below the acceptable values.
- Hands** : Gloves. (Fire resistant.)
- Feet** : Metal cap, safety boots.

Exposure limits	Exposure limits
Welding fumes	ACGIH TLV (United States). TWA: 5 mg/m <sup>3</sup> 8 hour(s). Form: Particulate.
Silica, Crystalline - Quartz	ACGIH TLV (United States, 1/2006). TWA: 0.025 mg/m <sup>3</sup> 8 hour(s). Form: Respirable fraction NIOSH REL (United States, 12/2001). TWA: 0.05 mg/m <sup>3</sup> 10 hour(s). OSHA PEL Z3 (United States, 9/2005). TWA: 10 mg/m <sup>3</sup> 8 hour(s). Form: Respirable
Chromium oxide	ACGIH TLV (United States, 1/2006). TWA: 0.5 mg/m <sup>3</sup> , (Measured as Cr) 8 hour(s). Form: Inorganic NIOSH REL (United States, 12/2001). TWA: 0.5 mg/m <sup>3</sup> , (as Cr) 10 hour(s). OSHA PEL (United States, 11/2006). TWA: 0.5 mg/m <sup>3</sup> , (as Cr) 8 hour(s).
Chromium (VI) trioxide	ACGIH TLV (United States, 1/2006). TWA: 0.05 mg/m <sup>3</sup> , (Measured as Cr) 8 hour(s). Form: Soluble OSHA PEL (United States, 11/2006). TWA: 1 mg/m <sup>3</sup> , (as Cr) 8 hour(s).
Alumina	ACGIH TLV (United States, 1/2006). TWA: 10 mg/m <sup>3</sup> 8 hour(s). NIOSH REL (United States, 12/2001). TWA: 5 mg/m <sup>3</sup> , (as Al) 10 hour(s). OSHA PEL (United States, 11/2006). TWA: 5 mg/m <sup>3</sup> 8 hour(s). Form: Respirable fraction
Titanium dioxide	ACGIH TLV (United States, 1/2006). TWA: 10 mg/m <sup>3</sup> 8 hour(s). OSHA PEL (United States, 11/2006). TWA: 15 mg/m <sup>3</sup> 8 hour(s). Form: Total dust
Molybdenum oxide	ACGIH TLV (United States, 1/2006). TWA: 3 mg/m <sup>3</sup> , (as Mo) 8 hour(s). Form: Insoluble OSHA PEL (United States, 11/2006). TWA: 15 mg/m <sup>3</sup> , (as Mo) 8 hour(s). Form: Total dust
Nickel oxide	ACGIH TLV (United States, 1/2006). TWA: 0.1 mg/m <sup>3</sup> , (as Ni) 8 hour(s). Form: Soluble OSHA PEL (United States, 11/2006). TWA: 1 mg/m <sup>3</sup> , (as Ni) 8 hour(s).
Zirconium oxide	ACGIH TLV (United States, 1/2006). STEL: 10 mg/m <sup>3</sup> , (as Zr) 15 minute(s). TWA: 5 mg/m <sup>3</sup> , (as Zr) 8 hour(s). NIOSH REL (United States, 12/2001). STEL: 10 mg/m <sup>3</sup> , (as Zr) 15 minute(s). TWA: 5 mg/m <sup>3</sup> , (as Zr) 10 hour(s). OSHA PEL (United States, 11/2006). TWA: 5 mg/m <sup>3</sup> , (as Zr) 8 hour(s).

**Consult local authorities for acceptable exposure limits.**

## Section 9. Physical and Chemical Properties

<b>Physical state and Appearance</b>	: Solid.
<b>Color</b>	: Gray.
<b>Odor</b>	: Odorless.
<b>Melting/freezing point</b>	: 1500°C (2732°F)
<b>Specific gravity</b>	: Weighted average: 7.21 (Water = 1)
<b>Solubility</b>	: Insoluble in the following materials: cold water, hot water.

## Section 10. Stability and Reactivity

<b>Stability and reactivity</b>	: The product is stable.
<b>Hazardous decomposition products</b>	: Metallic oxides. Carbon oxides (CO, CO <sub>2</sub> ). Arc radiation can support the production of ozone and nitrogen oxides.
<b>Hazardous polymerization</b>	: Will not occur.

## Section 11. Toxicological Information

### Additional Toxicity data

<u>Ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Not available.				

<b>Chronic effects and other toxic effects on humans</b>	: <b>CARCINOGENIC EFFECTS:</b> See Section 2. Contains material which causes damage to the following organs: blood, kidneys, lungs, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea, nose/sinuses. Acute exposure to welding fumes may result in discomfort such as: dizziness, nausea or dryness of nose, throat or the eyes.
--	--

## Section 12. Ecological Information

### Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Chromium, Metal	Daphnia magna (EC50)	48 hour(s)	0.07 mg/l
Manganese	Daphnia magna (EC50)	48 hour(s)	40 mg/l
Molybdenum	Oncorhynchus mykiss (LC50)	96 hour(s)	800 mg/l
Nickel	Daphnia magna (EC50)	48 hour(s)	1 mg/l

<b>Products of degradation</b>	: Some metallic oxides.
--------------------------------	-------------------------

## Section 13. Disposal Considerations

<b>Waste information</b>	: Waste must be disposed of in accordance with federal, state and local environmental control regulations. Recycle, if possible. <i>Consult your local or regional authorities.</i>
--------------------------	--

## Section 14. Transport Information

No transport class is found applicable to this product.

## Section 15. Regulatory Information

<b>HCS Classification</b>	: <b>These hazards relate to welding fumes (electrodes in use) and not to the electrodes as sold.</b>
---------------------------	---

Contains material which may cause cancer.  
Irritating material  
Sensitizing material  
Target organ effects

<b>U.S. Federal regulations</b>	: <b>United States inventory (TSCA 8b):</b> All components are listed or exempted.
---------------------------------	--

**Clean Water Act (CWA) 307:** Chromium; Nickel

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 accidental release prevention:** No products were found.

**Clean Air Act (CAA) 112 regulated flammable substances:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

**SARA 302/304/311/312 extremely hazardous substances:** No products were found.

**SARA 302/304 emergency planning and notification:** No products were found.

**SARA 302/304/311/312 hazardous chemicals:** Nickel; Titanium dioxide; Manganese; Molybdenum; Silica, Crystalline - Quartz

**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:** Iron: Fire hazard; Nickel: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; Titanium dioxide: Delayed (chronic) health hazard; Manganese: reactive, Immediate (acute) health hazard, Delayed (chronic) health hazard; Molybdenum: Immediate (acute) health hazard, Delayed (chronic) health hazard; Silica, Crystalline - Quartz: Immediate (acute) health hazard, Delayed (chronic) health hazard

### [SARA 313](#)

<b>Form R - Reporting requirements</b>	: Chromium, Metal Nickel Manganese	16-25 8-15 0.5-4
<b>Supplier notification</b>	: Chromium, Metal Nickel Manganese	16-25 8-15 0.5-4
<b>State regulations</b>	: <b>Massachusetts Substances:</b> The following components are listed: Chromium; Nickel; Titanium dioxide; Molybdenum; Manganese;Silica crystalline, quartz <b>New Jersey Hazardous Substances:</b> The following components are listed: Chromium; Nickel; Titanium dioxide; Molybdenum; Manganese;Silica crystalline, quartz <b>New York Acutely Hazardous Substances:</b> The following components are listed: Chromium;Nickel <b>Pennsylvania RTK Hazardous Substances:</b> The following components are listed: Chromium; Nickel; Titanium dioxide; Molybdenum; Manganese;Silica crystalline, quartz	
<b>WHMIS (Canada)</b>	: <b>These hazards relate to welding fumes (electrodes in use) and not to the electrodes as sold.</b>  Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).  <b>CEPA Toxic substances:</b> None of the components are listed. <b>Canadian ARET:</b> None of the components are listed. <b>Canadian NPRI:</b> The following components are listed: Chromium; Nickel;Manganese <b>Alberta Designated Substances:</b> None of the components are listed. <b>Ontario Designated Substances:</b> None of the components are listed. <b>Quebec Designated Substances:</b> None of the components are listed.  <b>This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.</b>	

## Section 16. Other Information

<b>Label requirements</b>	: See Section 2.
<b>Hazardous Material Information System (U.S.A.)</b>	: Health: 2* Fire: 0 Reactivity: 0
<b>National Fire Protection Association (U.S.A.)</b>	: Health: 2 Fire: 0 Reactivity: 0 Other: None
<b>References</b>	: - 29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG. - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005. - CRC Handbook of chemistry and physics, 67th edition. CRC Press inc., Boca Raton, Florida. - Manufacturer's Material Safety Data Sheet. ANSI Z400.5, MSDS Standard, 2004. ANSI Z49.1 Safety in Welding and Cutting, The American Welding Society, P.O. Box 351040, Miami, FL 33135. Canadian Standard Association, CSA W117.2, Code for Safety in Welding and Cutting, 2003.
<b>Abbreviations</b>	: <b>ACGIH: American Conference of Governmental Industrial Hygiene.</b> ACGIH A2--Suspected Human Carcinogen. ACGIH-A4-Not Classifiable as a Human Carcinogen. ACGIH-A5-Not suspected as a Human Carcinogen. <b>IARC: International Agency for Research on Cancer.</b> IARC 2A: Probable for human. IARC 2B: Possible for human. IARC 3: Not classifiable for human. <b>NIOSH: National Institute of Occupational Safety and Health.</b> NIOSH +: Proven. NIOSH: None. <b>NTP: National Toxicology program.</b> NTP 1: Known to be human carcinogens. NTP 2: Reasonably Anticipated to be human carcinogens.
<b>Responsible name</b>	: Atrion Regulatory Services, Inc.
<b>Date of previous issue</b>	: 09/30/2006
<b>Version</b>	: 3

### Notice to reader

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROM SOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, AIR LIQUIDE CANADA INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.